

Section I - IDENTIFICATION

TRADE NAME: RENEW COAT®

MANUFACTURER: Lambert Corporation
20 N. Coburn
Orlando, FL 32805

PREPARED BY: Steve Kuhle

PREPARATION DATE: 10/15/2007

TELEPHONE NUMBER: (407) 841-2940

EMERGENCY NUMBER: (800) 424-9300 - Chemtrec



Section II - HAZARDOUS INGREDIENTS

<u>Ingredients</u>	<u>CAS NUMBER</u>	<u>PEL</u> <u>OSHA (PPM)</u>	<u>TLV:</u> <u>ACGIH (PPM)</u>	<u>OTHER</u> <u>LIMITS</u>
Silica - Crystalline Quartz	14808-60-7	0.1 mg/m ³	0.1 mg/m ³	
Mineral Oil Mist	OP0273	5 mg/m ³	5 mg/m ³	
Silicon Dioxide - Amorphous (SiO ₂)	7631-86-9	6 mg/m ³	10 mg/m ³	
Portland Cement	65997-15-1	10 mg/m ³	30 mppcf	*See Note
Calcium Carbonate	1317-65-3	5 mg/m ³	10 mg/m ³	
Lithium Carbonate Li ₂ CO ₃	554-12-2	N/E	N/E	
Citric Acid	77-92-9	N/E	N/E	
Aluminum Oxide	1344-28-1	N/E	N/E	
Iron Oxide	1309-37-1	10 mg/m ³	10 mg/m ³	
Titanium Dioxide	13463-67-7	15 mg/m ³	10 mg/m ³	

Note*: Portland Cement may or may not contain trace amounts of free crystalline silica found to be hazardous or toxic in some chemical forms, and are recognized as a human carcinogen.

GENERAL INFORMATION: This document supersedes all previous versions. To the best of our knowledge the information contained herein is correct. Lambert Corporation of Florida, Inc. assumes no responsibility for accuracy or completeness. User is responsible for suitability.

HMIS	
Health	1
Flammability	0
Reactivity	0
Personal Protection	E

Section III - PHYSICAL DATA / CHEMICAL CHARACTERISTICS

<i>Boiling Point</i>	N/A	<i>Specific Gravity (H₂O = 1):</i>	2.2 - 3.0
<i>Vapor Pressure (mm Hg):</i>	N/A	<i>Melting Point</i>	N/A
<i>Vapor Density (AIR=1):</i>	N/A	<i>Evaporation Rate (Butyl Acetate = 1):</i>	N/A
<i>Solubility in Water:</i>	Slightly Soluble	<i>Appearance and Odor:</i>	Grey Powder, No Odor

Section IV - FIRE AND EXPLOSION HAZARD DATA

<i>Flash Point (Method Used):</i>	NON-FLAMMABLE		
<i>Flammable Limits:</i>	N/A	<i>LEL:</i>	N/A
		<i>UEL:</i>	N/A
<i>Extinguishing Media:</i>	NO FIRE OR EXPLOSION DANGER. USE EXTINGUISHING MEDIA SUITABLE FOR SURROUNDING FIRE AND MATERIALS.		
<i>Special Fire Fighting Procedures:</i>	WATER MAY CAUSE MATERIAL TO SET-UP. A SLURRY OF MATERIAL CAN PLUG DRAINS. WET CEMENT CAN DRY SKIN AND CAUSE ALKALI BURNS		
<i>Unusual Fire and Explosion Hazards:</i>	NONE		

Section V - REACTIVITY DATA

Stability: **STABLE**

Incompatibility (Conditions or Materials to Avoid): ACID

Hazardous Decomposition of Byproducts:

Hazardous Polymerization: **WILL NOT OCCUR**

Conditions to Avoid: PRODUCT SHOULD BE KEPT DRY UNTIL USED.

Section VI - HEALTH HAZARD DATA*Routes of Entry:*

Eyes: DUST IRRITANT

Inhalation: AVOID OVER EXPOSURE

Skin: ABRASIVE

Ingestion: MAY CAUSE OBSTRUCTION. INGESTION UNLIKELY

Health Data Comment - Additional:

ACUTE: INHALATION OF SILICA DUST CAN PRODUCE SILICOSIS, WHICH IS A SLOWLY DEVELOPING DISEASE. AVOID OVER-EXPOSURE TO THE AIRBORNE DUST. WET CEMENT CAN DRY THE SKIN AND CAUSE ALKALI BURNS. CEMENT DUST CAN IRRITATE THE EYES AND UPPER RESPIRATORY SYSTEM.

CHRONIC: CEMENT DUST CAN CAUSE INFLAMMATION OF THE LINING TISSUE OF THE INTERIOR OF THE NOSE AND INFLAMMATION OF THE CORNEA. HYPERSENSITIVE INDIVIDUALS MAY DEVELOP AN ALLERGIC DERMATITIS.

Carcinogenicity: CLASSIFIED YES
 NTP: YES
 IARC Monographs: LIMITED EVIDENCE AS CARCINOGEN
 OSHA Regulated: YES

Signs and Symptoms of Exposure:

IRRITATION, REDNESS, OR BURNING OF EYES. SHORTNESS OF BREATH, COUGHING, OR BREATHING SYSTEMS BEYOND THAT OF A NORMAL COLD. REDNESS AND/OR SWELLING OF SKIN.

Medical Conditions Generally Aggravated by Exposure:

EXTREMELY SENSITIVE SKIN AND BREATHING OR RESPIRATORY CONDITIONS

Emergency & First Aid Procedures:

Ingestion: MAY CAUSE OBSTRUCTION, ALTHOUGH UNLIKELY IN NORMAL USE. IF INGESTED SEEK MEDICAL HELP. DO NOT INDUCE VOMITING AS IT MAY CAUSE ASPIRATION OF SUBSTANCE.

Eyes: FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. IF IRRITATION PERSISTS SEEK MEDICAL HELP.

Skin: WASH THOROUGHLY WITH SOAP AND WATER. IF IRRITATION PERSISTS SEEK MEDICAL HELP.

Inhalation: REMOVE TO FRESH AIR. IF NECESSARY SEEK MEDICAL HELP.

Section VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be taken in case Material is released or spilled:

COLLECT WITH NORMAL SWEEP/CLEAN UP METHODS. AVOID CREATING EXCESSIVE DUST. DO NOT ADD WATER AS THIS MAY CAUSE PRODUCT TO SET-UP.

Waste Disposal Method:

FOLLOW LOCAL, STATE, AND FEDERAL REGULATIONS REGARDING DISPOSAL OF PRODUCT.

Precautions to be Taken in Handling and Storage:

CONTROL DUST BY USING VACUUM CLEAN-UP SYSTEM. KEEP DRY UNTIL USED.

Other Precautions:

DO NOT EXPOSE FOOD, DRINK, OR TOBACCO/CHEWING PRODUCT TO DUST. TAKE STEPS TO PROTECT SKIN AND EYES FROM CONTACT AND TO MINIMIZE INHALATION.

FOR INDUSTRIAL USE ONLY**Section VIII - CONTROL MEASURES**

Respiratory Protection (Type):

USED NIOSH/OSHA APPROVED RESPIRATOR

Ventilation: Local Exhaust:

KEEP DUST FROM BECOMING AIRBORNE

Mechanical (General):

N/A

Special:

CONSTANT FLOW OF FRESH AIR IN AREA IS SUGGESTED.

Other:

Protective Gloves:

BARRIER CREAM, NEOPRENE, OR RUBBER GLOVES

Eye Protection:

SAFETY GOGGLES SUGGESTED.

Other Protective Clothing or Equipment:

HAVE AN EYEBATH(S) AND WASHING FACILITIES IN THE AREA.

Work/Hygienic Practices:

PRACTICE GOOD HYGIENE. WASH HANDS THOROUGHLY BEFORE EATING, DRINKING, OR USING TOBACCO PRODUCTS. PRACTICE GOOD HOUSEKEEPING.