

[Close this window](#)

SDS

Common Name: TFE PIPE THREAD SEALANT W/PTFE**Manufacturer:** ANTI-SEIZE TECHNOLOGY**SDS Revision Date:** 12/9/2014**SDS Format:** GHS-US**Grainger Item Number(s):** 4UJ90, 4X222, 5X998**Manufacturer Model Number(s):**

SDS Table of Contents

Click the desired link below to jump directly to that section in the SDS.

[SECTION 1: IDENTIFICATION](#)[SECTION 2: HAZARDS IDENTIFICATION](#)[SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS](#)[SECTION 4: FIRST AID MEASURES](#)[SECTION 5: FIRE-FIGHTING MEASURES](#)[SECTION 6: ACCIDENTAL RELEASE MEASURES](#)[SECTION 7: HANDLING AND STORAGE](#)[SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION](#)[SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES](#)[SECTION 10: STABILITY AND REACTIVITY](#)[SECTION 11: TOXICOLOGICAL INFORMATION](#)[SECTION 12: ECOLOGICAL INFORMATION](#)[SECTION 13: DISPOSAL CONSIDERATIONS](#)[SECTION 14: TRANSPORT INFORMATION](#)[SECTION 15: REGULATORY INFORMATION](#)[SECTION 16: OTHER INFORMATION](#)

A

ANTI-SEIZE TECHNOLOGY

A.S.T. INDUSTRIES, INC.

TFE (TM) PIPE THREAD SEALANT W/PTFE

SAFETY DATA SHEET

SECTION 1: IDENTIFICATION



PRODUCT NAME: TFE (TM) PIPE THREAD SEALANT W/PTFE

MANUFACTURER:

ANTI-SEIZE TECHNOLOGY

2345 N. 17TH AVE.

FRANKLIN PARK, IL 60131

PHONE: 847-455-2300

TOLL FREE: 800 991-1106

WEB: ANTISEIZE.COM

INFORMATION PHONE NUMBER:

EMERGENCY PHONE NUMBER:

INFOTRAC 24/7 PHONE: 1-800-535-5053 OR 352-323-3500

PRODUCT USE: PIPE THREAD SEALANT

RESTRICTION ON USE: NONE KNOWN

SDS DATE OF PREPARATION: DECEMBER 09, 2014

SECTION 2: HAZARDS IDENTIFICATION



GHS CLASSIFICATION (HAZCOM 2012): NOT HAZARDOUS

LABEL ELEMENTS:

NOT HAZARDOUS IN ACCORDANCE WITH THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200).

HAZARD PHRASES: NONE

PRECAUTIONARY PHRASES: NONE

OTHER HAZARDS: NONE

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS



| CHEMICAL NAME | CAS# | % |
|---|------------|-------|
| KAOLIN CLAY | 1332-58-7 | 35-45 |
| DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC | 64742-52-5 | 15-30 |
| CALCIUM CARBONATE | 471-34-1 | 10-15 |
| TITANIUM DIOXIDE (BOUND IN SEALANT) | 13463-67-7 | 5-10 |
| PTFE | 9002-84-0 | 10-20 |

THE SPECIFIC IDENTITY AND/OR EXACT PERCENTAGE OF COMPOSITION HAS BEEN WITHHELD AS A TRADE SECRET.

SECTION 4: FIRST AID MEASURES



EYE:

FLUSH EYES WITH WATER, HOLDING THE EYELIDS APART. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS OR PERSISTS.

SKIN:

WASH THOROUGHLY WITH PLENTY OF WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

INHALATION:

REMOVE TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING. IF IRRITATION OCCURS, GET MEDICAL ATTENTION.

INGESTION: IF LARGE AMOUNTS INGESTED, SEEK MEDICAL ATTENTION.

MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED: NONE KNOWN.

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED:
IMMEDIATE MEDICAL ATTENTION GENERALLY NOT REQUIRED.

SECTION 5: FIRE-FIGHTING MEASURES



SUITABLE AND UNSUITABLE EXTINGUISHING MEDIA:
USE EXTINGUISHING MEDIA SUITABLE FOR THE SURROUNDING ENVIRONMENT.

SPECIAL HAZARDS ARISING FROM THE CHEMICAL:
HAZARDOUS DECOMPOSITION PRODUCTS MAY YIELD OXIDES OF CARBON AND CALCIUM, AND FUMES OF FLUORIDES.

SPECIAL EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS:
WEAR NIOSH APPROVED POSITIVE PRESSURE, SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING. COOL FIRE EXPOSED CONTAINERS WITH WATER.

SECTION 6: ACCIDENTAL RELEASE MEASURES



PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:
WEAR APPROPRIATE PERSONAL PROTECTIVE EQUIPMENT.

USE CAUTION: SLIP HAZARD.

ENVIRONMENTAL HAZARDS:
REPORT SPILLS AND RELEASES AS REQUIRED TO APPROPRIATE AUTHORITIES.

METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:
BECAUSE OF ITS VISCOUS NATURE, THIS PRODUCT IS NOT EXPECTED TO LEAK OR SPILL. COLLECT LIQUID SPILL WITH AN INERT ABSORBENT MATERIAL AND PLACE INTO A SUITABLE CONTAINER FOR DISPOSAL. CLEAN AREA THOROUGHLY WITH MINERAL SPIRITS.

SECTION 7: HANDLING AND STORAGE



PRECAUTIONS FOR SAFE HANDLING:
AVOID CONTACT WITH EYES. AVOID PROLONGED SKIN CONTACT. DO NOT TRANSFER TO UNLABELED CONTAINERS.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:
STORE AWAY FROM EXTREME HEAT AND OPEN FLAMES. STORE AWAY FROM CONCENTRATED OXYGEN.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION



| CHEMICAL NAME | EXPOSURE LIMITS |
|---------------|--|
| KAOLIN CLAY | 2 MG/M3 TWA ACGIH TLV (RESPIRABLE) |
| | 15 MG/M3 TWA OSHA PEL (TOTAL DUST) |
| | 5 MG/M3 TWA OSHA PEL (RESPIRABLE FRACTION) |

| | |
|---|--|
| DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC | 5 MG/M3 TWA ACHIH TLV (INHALABLE) 5 MG/M3 TWA OSHA PEL |
| CALCIUM CARBONATE | 15 MG/M3 TWA OSHA PEL (TOTAL DUST) 5 MG/M3 TWA OSHA PEL (RESPIRABLE FRACTION) |
| TITANIUM DIOXIDE | 10 MG/M3 TWA ACGIH TLV (RESPIRABLE) 15 MG/M3 TWA OSHA PEL (TOTAL DUST) |

APPROPRIATE ENGINEERING CONTROLS:

USE WITH ADEQUATE GENERAL OR LOCAL EXHAUST VENTILATION TO MAINTAIN EXPOSURE LEVELS BELOW THE EXPOSURE LIMITS. IF THE PRODUCT IS USED AT HIGH TEMPERATURES, LOCAL EXHAUST VENTILATION MAY BE REQUIRED.

INDIVIDUAL PROTECTION MEASURES:**RESPIRATORY PROTECTION:**

IN OPERATIONS WHERE THE OCCUPATIONAL EXPOSURE LIMITS ARE EXCEEDED, A NIOSH APPROVED RESPIRATOR WITH ORGANIC VAPOR/PARTICULATE CARTRIDGES OR SUPPLIED AIR RESPIRATOR APPROPRIATE FOR THE FORM AND CONCENTRATION OF THE CONTAMINANTS SHOULD BE USED. SELECTION AND USE OF RESPIRATORY EQUIPMENT MUST BE IN ACCORDANCE WITH OSHA 1910.134 AND GOOD INDUSTRIAL HYGIENE PRACTICE.

SKIN PROTECTION:

IMPERVIOUS GLOVES SUCH AS RUBBER OR NITRILE RECOMMENDED WHERE NEEDED TO AVOID PROLONGED SKIN CONTACT.

EYE PROTECTION:

SAFETY GLASSES OR GOGGLES RECOMMENDED WHERE NEEDED TO AVOID EYE CONTACT.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: WHITE GRANULAR PASTE

VAPOR DENSITY (AIR = 1): NOT AVAILABLE

ODOR: MILD PETROLEUM LIKE ODOR

SPECIFIC GRAVITY: 1.5

ODOR THRESHOLD: NOT ESTABLISHED

WATER SOLUBILITY: NOT SOLUBLE

PH: NEUTRAL

OCTANOL/WATER PARTITION COEFFICIENT: NOT AVAILABLE

MELTING POINT/FREEZING POINT: NOT AVAILABLE

AUTOIGNITION TEMPERATURE: NOT AVAILABLE

BOILING POINT: >650 DEG. F

DECOMPOSITION TEMPERATURE: NOT AVAILABLE

FLASH POINT: >350 DEG. F

VISCOSITY: NOT AVAILABLE

EVAPORATION RATE: NOT AVAILABLE

EXPLOSION PROPERTIES: NONE

FLAMMABLE LIMITS:

LEL: NOT ESTABLISHED

UEL: NOT ESTABLISHED

OXIDIZING PROPERTIES: NOT OXIDIZING

VAPOR PRESSURE: NOT ESTABLISHED

AEROSOL FIRE PROTECTION LEVEL: NOT APPLICABLE

VOC CONTENT: <0.1%

FLAMMABILITY (SOLID, GAS): NOT AVAILABLE

SECTION 10: STABILITY AND REACTIVITY



REACTIVITY: NOT REACTIVE UNDER NORMAL CONDITIONS OF USE.

CHEMICAL STABILITY: STABLE UNDER NORMAL STORAGE AND HANDLING CONDITIONS.

POSSIBILITY OF HAZARDOUS REACTIONS: NONE KNOWN

CONDITIONS TO AVOID: TEMPERATURES EXCEEDING 550 DEG. F

INCOMPATIBLE MATERIALS: AVOID CONCENTRATED OXYGEN

HAZARDOUS DECOMPOSITION PRODUCTS:

HAZARDOUS DECOMPOSITION PRODUCTS MAY YIELD OXIDES OF CARBON AND CALCIUM, AND FUMES OF FLUORIDES.

SECTION 11: TOXICOLOGICAL INFORMATION



POTENTIAL HEALTH EFFECTS:

EYE: MAY CAUSE MILD IRRITATION.

SKIN: PROLONGED CONTACT MAY CAUSE IRRITATION AND DRYING OF THE SKIN.

INHALATION:

NO ADVERSE EFFECTS EXPECTED AT AMBIENT TEMPERATURES. INHALATION OF VAPORS AND FUMES FROM THERMAL DECOMPOSITION MAY CAUSE RESPIRATORY IRRITATION.

INGESTION:

SWALLOWING MAY CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, DIARRHEA.

CHRONIC HAZARDS:

PROLONGED INHALATION OF THERMAL DECOMPOSITION PRODUCTS MAY RESULT IN LUNG DAMAGE.

CARCINOGEN STATUS:

TITANIUM DIOXIDE IS LISTED BY IARC AS A GROUP 2B CARCINOGEN (POSSIBLE HUMAN CARCINOGEN). TITANIUM DIOXIDE IS ONLY KNOWN TO CAUSE CANCER BY INHALATION. THE TITANIUM DIOXIDE IS BOUND IN THE PRODUCT MATRIX SO INHALATION EXPOSURE DOES NOT OCCUR DURING USE. NONE OF THE OTHER COMPONENTS OF THIS PRODUCT ARE

LISTED AS CARCINOGENS BY OSHA, IARC, NTP, ACGIH, OR THE EU CLP.

ACUTE TOXICITY VALUES:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC:

ORAL RAT LD50: >5000 MG/KG

INHALATION RAT LC50: 2.18 MG/L

DERMAL RABBIT LD50: >2000 MG/KG

CALCIUM CARBONATE:

ORAL RAT LD50: >2000 MG/KG

INHALATION RAT LC50: >3 MG/L

DERMAL RAT LD50: >2000 MG/KG

TITANIUM DIOXIDE:

ORAL MOUSE LD50: >5000 MG/KG

INHALATION RAT LC50: >6.82 MG/L

SECTION 12: ECOLOGICAL INFORMATION



ECOTOXICITY:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC:

PIMEPHALES PROMELAS LL50: >100 MG/L/96HR.

CALCIUM CARBONATE:

ONCORHYNCHUS MYKISS LC50: >100 MG/L/96HR

PERSISTENCE AND DEGRADABILITY: NO DATA AVAILABLE

BIOACCUMULATIVE POTENTIAL: NO DATA AVAILABLE

MOBILITY IN SOIL: NO DATA AVAILABLE

OTHER ADVERSE EFFECTS: NONE KNOWN

SECTION 13: DISPOSAL CONSIDERATIONS



DISPOSE IN ACCORDANCE WITH ALL LOCAL, REGIONAL AND NATIONAL REGULATIONS. DO NOT PUNCTURE OR INCINERATE CONTAINERS. WHEN CONTENTS ARE DEPLETED, CONTINUE TO DEPRESS BUTTON UNTIL ALL GAS IS EXPELLED.

SECTION 14: TRANSPORT INFORMATION



DOT PROPER SHIPPING NAME: NOT REGULATED

DOT TECHNICAL NAME: NONE

DOT HAZARD CLASS: NONE

UN NUMBER: NONE

DOT LABELS REQUIRED (49 CFR 172.101): NONE

IMDG SHIPPING DESCRIPTION: NOT REGULATED

ID NUMBER: NONE

HAZARD CLASS: NONE

PACKING GROUP: NONE
LABELS REQUIRED: NONE
MARKING REQUIRED: NONE
PLACARDS REQUIRED: NONE

SECTION 15: REGULATORY INFORMATION



SAFETY, HEALTH, AND ENVIRONMENTAL REGULATIONS SPECIFIC FOR THE PRODUCT IN QUESTION.

CERCLA HAZARDOUS SUBSTANCES (SECTION 103)/RQ:
THIS PRODUCT IS NOT SUBJECT TO REPORTING REQUIREMENTS UNDER CERCLA. HOWEVER, MANY STATES HAVE MORE STRINGENT RELEASE REPORTING REQUIREMENTS. REPORT SPILLS REQUIRED UNDER FEDERAL, STATE AND LOCAL REGULATIONS.

SARA HAZARD CATEGORY (311/312): NOT HAZARDOUS

SARA 313:
THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS REGULATED UNDER SARA TITLE III, SECTION 313: NONE

EPA TSCA INVENTORY:
ALL OF THE COMPONENTS OF THIS PRODUCT ARE LISTED ON THE TSCA INVENTORY.

CALIFORNIA PROPOSITION 65:
THIS PRODUCT IS NOT KNOWN TO CONTAIN LISTED CHEMICALS.

SECTION 16: OTHER INFORMATION



REVISION SUMMARY: NEW FORMAT TO COMPLY WITH OSHA HAZCOM 2012

NOTICE TO READER:
TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE. HOWEVER, NEITHER THE ABOVE-NAMED SUPPLIER, NOR ANY OF ITS SUBSIDIARIES, ASSUMES ANY LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. FINAL DETERMINATION OF SUITABILITY OF ANY MATERIAL IS THE SOLE RESPONSIBILITY OF THE USER. ALL MATERIALS MAY PRESENT UNKNOWN HAZARDS AND SHOULD BE USED WITH CAUTION. ALTHOUGH CERTAIN HAZARDS ARE DESCRIBED HEREIN, WE CANNOT GUARANTEE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.